Lokotrack[®] ST2.8[™] & ST2.8E Areas of application: Biggest eccentric throw on the market Primary scalping ST2.8TM offers high capacity with most aggressive stroke on the market that makes liozaoT it very efficient in scalping sticky material like topsoil, river gravel or slag. Feeder start/stop Recycled waste To be connected with Lokotrack LT crusher Large hopper with side walls Separation of metal particles Road base To be fed with wheel loader or excavator Magnetic drums • Magnetic separator Fine aggregates Wide selection of screening media High fuel efficiency engine CAT[®] Diesel-Electric Two-way split option drive with e-Power * Combines materials from decks to improve capacity Heavy duty air filter Protects engine from dust Metso Outotec IC automation and reduces service interval Easy and safe process control and connectivity to other Lokotracks Easy to transport Easy maintenance access Optimized weight and dimensions Hydraulic screen lift and large area under screen *Available as an option Easy to transport Diesel-electric drive Biggest stroke for sticky material Easy to use and service with e-Power

Technical details Lokotrack[®] ST2.8[™] & ST2.8E

Metso:Outotec

Screen



Size 4,860 x 1,520 mm (16' x 5')

Screening area 7.4 m² (8.9 yd²)

Decks

2

Nominal capacity* 600 Mtph (660 Stph)

Stroke Up to 15 mm

Screening media Woven steel mesh, Plate grizzly, Finger grizzly, Punch plate



Type Belt or Apron feeder Hopper volume

4.5 m³ (5.9 yd³) standard 11 m³ (14.3 yd³) extensions

Loading height 3,300 / 3,680 mm (10' 10" / 11' 1")

Loading width 3,000 mm (9' 10")

Max feed size 600 mm (24") Conveyor



Conveyor oversize width 1,200 mm (47")

Side conveyor midsize width 800 mm (31,5") Adjustable discharge height

Side conveyor undersize width 800 mm (31,5") Adjustable discharge height

Under screen conveyor width 1,200 mm (47") Engine power options



Model CAT® C3.6

StageV/Tier4F 100 kW (134 hp)

Tier3 98 kW (131 hp)

Fuel tank 300 | (79 gal)

Hydraulic oil 105 | (28 gal)

*Available as an option

Transport dimensions



Length 15,400 mm (50' 7")

Width 3,000 mm (9' 10")

Height 3,560 mm (11' 8")

Weight 26,000 kg (57,300 lbs)

*Capacity depends on application (required end products, feed material characteristics and size, moisture etc.)



Aggressive stroke for sticky material.



World class expertize for tailored options.



Easy to combine with other Lokotracks.



"My experience with Metso equipment is that it's pretty much hands-on, it's easy to use. The whole process of operating the equipment is much easier than other brands that I've used." Jason Cash, Cranford, Georgia, USA.