

MELLOTT

TECHNICAL DATA – MC106P



VIBRATING GRIZZLY FEEDER

- 42"x17' Vibrating Feeder
- 5' Grizzly Section w/ Adjustable Bars
- 12' Long Pan w/ Replaceable ½" AR Liners
- 40 HP, 1200 RPM, TEFC Electric Motor

JAW CRUSHER

- Metso C106 Jaw w/ Integral Motor Mount
- Feed Opening 42" Wide x 28" Deep
- 150 HP, 1200 RPM TEFC Crusher Duty Motor
- Closed Side Setting 2 ¾" – 8"
- Composite Guards, Crusher Feed Chute

CHASSIS

- Heavy Duty Fabricated Frame Complete w/ Cribbing Supports
- Tri-Axle Suspension w/ Twelve 11R24.5 Tires
- Road Ready w/ Airbrakes and Mud Flaps

UNDER CRUSHER CONVEYOR

- 42" BW x 30' Long Conveyor
- 15 HP Motorized Head Pulley
- Channel Frame Construction
- CEMA C5 Idlers
- 4' Long Impact Bed at Loading Zone

AVAILABLE OPTIONS

- Pre-Wired Plant with Electric Starter Panel
- Hydraulic Lifting Legs
- 5' Long Enlarged Hopper (BW+12")
- 10' Long Skirtboard Extension
- Scraper
- Discharge Chute
- 3-PLY, 330 PIW Belting
- CEMA C5 Idlers

